

F-FAB Series

 CAPACITY CHART		F-FAB 6-100	F-FAB 10-100	F-FAB 12-100	F-FAB 16-100	F-FAB 20-100	F-FAB 10-150	F-FAB 12-150	F-FAB 16-150	F-FAB 20-150	F-FAB 10-200	F-FAB 12-200	F-FAB 16-200	F-FAB 20-200
Bending Length		6'	10'	12'	16'	20'	10'	12'	16'	20'	10'	12'	16'	20'
Aluminum 5754-H22		12 Ga	14 Ga	14 Ga	16 Ga	16 Ga	0.156	0.156	0.125	0.125	0.250	0.250	0.210	0.210
Aluminum 6061-T6		14 Ga	16 Ga	16 Ga	18 Ga	18 Ga	0.125	0.125	12 Ga	12 Ga	0.210	0.210	0.187	0.187
Mild Steel		14 Ga	16 Ga	16 Ga	18 Ga	18 Ga	0.125	0.125	12 Ga	12 Ga	0.210	0.210	0.187	0.187
Titanium 6242		16 Ga	20 Ga	20 Ga	22 Ga	22 Ga	14 Ga	14 Ga	16 Ga	16 Ga	10 Ga	10 Ga	12 Ga	12 Ga
Upper Roll		1.00	1.00	1.00	1.00	1.00	1.50	1.50	1.50	1.50	2.00	2.00	2.00	2.00
Lower Rolls		1.75	1.75	1.75	1.75	1.75	2.00	2.00	2.00	2.00	2.36	2.36	2.36	2.36
Max. Pass Through		2.00	2.00	2.00	2.00	2.00	2.50	2.50	2.50	2.50	3.00	3.00	3.00	3.00
Length		139	187	211	259	307	187	211	259	307	190	141	262	310
Width		34	34	34	34	34	34	34	34	34	44	44	44	44
Height		84	84	84	84	84	84	84	84	84	96	96	96	96
Working Height		39.37	39.37	39.37	39.37	39.37	39.37	39.37	39.37	39.37	39.37	39.37	39.37	39.37
Weight		4,270	5,823	6,600	8,153	9,706	10,390	11,660	14,190	16,730	14,960	16,720	20,240	23,760
Motor Power		5.5	5.5	5.5	5.5	5.5	9.0	9.0	9.0	9.0	13.5	13.5	13.5	13.5

Due to ongoing product development, machine specifications can change at any time.