

B-GIANT SERIES	Standard Machine Characteristics												Below Grade		Ram Speeds Programmable				Back Guage System						Machine Dimensions			
	Bending Force	Bending Length	Distance Between Frames	Length of Ram Stroke	Daylight	Throat Depth	Bed Height	Standard Bed Cap Width	Optional (Common) Bed Cap Width's	# Sliding Front Support Arms	Motor Power	Oil Tank Capacity	Depth of Pit		Y-Axis Approach Speed	Y-Axis Forming Speed (+) Depends on Application	Decompression	Y-Axis Return Speed	X-Axis Speed	X-Axis Travel	Gaugeable with 3rd Finger Position	CNC Backguage R-Axis Max. Speed	CNC R-Axis Travel	# Backguage Finger Blocks	Length	Width	Height	Approx. Weight
	(US)	A	B	C	D	E	F	G1	G2	QTY			P1	P2	Prog.	Prog.	Prog.	Prog.	Prog.	Prog.	Prog.	Std.	Std.	QTY	L	W	H	Lbs
	Model Number	Tons	Feet	Feet	Inch	Inch	Inch	Inch	Inch	Inch	Pcs.	HP	Gal	Inch	Inch	I.P.M	I.P.M	I.P.M	I.P.M	I.P.M	Inch	Inch	I.P.M	Inch	Pcs.	Inch	Inch	Inch
B-GIANT 14660	660	14'1"	12'4"	15.2"	24.4"	20.1"	47.2"	12.0"	19.7"	2	60	132	-	-	0-213	0-19 (+)	0-19	20-165	1-709	39"	49"	1-189	10"	2	213"	94"	157"	92400
B-GIANT 20660	660	20'	16'8"	15.2"	24.4"	20.1"	41.3"	12.0"	19.7"	4	60	132	14.6"	45.3"	0-213	0-19 (+)	0-19	20-166	1-709	39"	49"	1-189	10"	4	283"	94"	163"	121000
B-GIANT 20900	900	20'	16'8"	19.7"	29.5"	29.5"	41.3"	12.0"	19.7"	4	60	185	23.6"	47.2"	0-165	0-14 (+)	0-14	18-142	1-709	39"	49"	1-189	10"	4	283"	110"	187"	154000
B-GIANT 23900	900	23'3"	16'8"	19.7"	29.5"	29.5"	41.3"	12.0"	19.7"	4	60	185	23.6"	47.2"	0-165	0-14 (+)	0-14	18-142	1-709	39"	49"	1-189	10"	4	323"	110"	187"	160600
B-GIANT 26900	900	26'6"	19'10"	19.7"	29.5"	29.5"	41.3"	12.0"	19.7"	4	60	185	27.6"	66.9"	0-165	0-14 (+)	0-14	18-142	1-709	39"	49"	1-189	10"	4	362"	110"	197"	189200
B-GIANT 201100	1100	20'	16'8"	19.7"	29.5"	29.5"	31.5"	19.7"	Request	4	75	238	27.6"	59.1"	0-165	0-14 (+)	0-14	18-142	1-709	49"	59"	1-189	10"	4	283"	114"	193"	176000
B-GIANT 231100	1100	23'3"	16'8"	19.7"	29.5"	29.5"	31.5"	19.7"	Request	4	75	238	27.6"	59.1"	0-165	0-14 (+)	0-14	18-142	1-709	49"	59"	1-189	10"	4	323"	114"	193"	184800
B-GIANT 261100	1100	26'6"	19'10"	19.7"	29.5"	29.5"	31.5"	19.7"	Request	4	75	238	27.6"	74.8"	0-165	0-14 (+)	0-14	18-142	1-709	49"	59"	1-189	10"	4	362"	118"	197"	211200
B-GIANT 231400	1400	23'3"	16'8"	19.7"	29.5"	29.5"	31.5"	19.7"	Request	4	100	264	27.6"	74.8"	0-165	0-12(+)	0-12	18-142	1-709	49"	59"	1-189	10"	4	323"	126"	197"	209000
B-GIANT 261400	1400	26'6"	19'10"	19.7"	29.5"	29.5"	31.5"	19.7"	Request	4	100	264	27.6"	86.6"	0-165	0-12(+)	0-12	18-142	1-709	49"	59"	1-189	10"	4	362"	126"	205"	286000
B-GIANT 261800	1800	26'6"	20'	23.6"	33.5"	29.5"	39.4"	19.7"	Request	4	120	330	39.4"	63.0"	0-165	0-12(+)	0-12	18-142	1-189	59"	79"	1-59	15.7"	4	362"	132"	220"	341000
B-GIANT 262200	2200	26'6"	20'	23.6"	33.5"	29.5"	41.3"	19.7"	Request	4	180	396	39.4"	78.7"	0-165	0-12(+)	0-12	18-142	1-189	59"	69"	1-59	15.7"	4	362"	146"	228"	393800
	2200+	26+	Please Consult your Dealer or RMT representative																									