



SPECIFICATIONS

Prices may be listed on a separate quotation page.
 Prices and specifications are subject to change without notice.
 Prices MIGHT NOT INCLUDE freight, handling and applicable taxes.

844.RMT.INFO
www.RMTUS.com

Profile Type			A-ECO 196		Notes
			Dimensions	Min. Internal Diameter	
1	Solid - Square		1-3/8" x 1-3/8" 3/4" x 3/4"	36" 12"	○
2	Flat-Along Edge		2-3/8" x 3/8"	20"	○
3	Solid - Rectangle		4" x 5/8"	18"	○
4	Angle Leg-Out		2" x 2" 3/16"	32"	○●
5	Angle Leg-In		2" x 2" 1/4"	40"	○●X
6	T Section Leg-Down		2-3/8" x 2-3/8" x 1/4"	28"	○
7	T Section Leg-Out		2-3/8" x 2-3/8" x 1/4"	28"	○
8	T Section Leg-In		2-3/8" x 2-3/8" x 1/4"	28"	○
9	Tubing - Square		2" x 2" x 0.120"	68" ∞	○●
10	Tubing - Rectangle		2-3/4" x 1-1/4" x 0.080"	48" ∞	○●
11	Solid - Round		∅1-3/8"	24"	○●
12	Schedule 40 Pipe		1" SCH 40 2" SCH 40	14" ∞ 40" ∞	●
13	Tubing - Round		∅1-1/4" x 0.080" ∅2-3/4" x 0.080"	20" ∞ 40" ∞	●
14	C Section Leg-Out		3"	40"	○●
15	C Section Leg-In		3"	48"	○●

RMT Profile Rolls A-ECO 196



STANDARD SPECIFICATIONS:

- Steel frame
- Two rolls direct driven by a gear system
- Rolls are hardened
- Rolls shafts are special steel material hardened and ground
- Roll shafts housed by bearings
- Standard rolls
- Guide rolls
- Horizontal and vertical working position

OPTIONS:

- Pipe/Tube bending rolls
- Profile bending rolls
- Angle bending rolls
- Digital readout
- Special lateral angle guide rolls

Capacity based on mild steel | ∞ Can be changed according to deformation
 ○ Standard Rolls | ● Special Rolls | X Special Support Rolls | ▲ Special Tools

Shaft Diameters: 1.96"
 Roll Diameters: 6.10"
 Motor Power: 2 HP
 Turning Speed: 14 FPM
 Dimensions: 30" L x 40" W x 56" H
 Weight: 881 lbs.