


















SPECIFICATIONS

Prices may be listed on a separate quotation page.
 Prices and specifications are subject to change without notice.
 Prices **MIGHT NOT INCLUDE** freight, handling and applicable taxes.

844.RMT.INFO
www.RMTUS.com

Profile Type		A-ECO 196 H		Notes
		Dimensions	Min. Internal Diameter	
1	Solid - Square	 1-3/8" x 1-3/8" 5/8" x 5/8"	24" 12"	○
2	Flat-Along Edge	 2-3/8" x 3/8"	24"	○
3	Solid - Rectangle	 4" x 5/8"	24"	○
4	Angle Leg-Out	 2" x 2" 1/4"	24"	○●
5	Angle Leg-In	 2" x 2" 1/4"	36"	○●X
6	T Section Leg-Down	 2-3/8" x 2-3/8" x 1/4"	32"	○
7	T Section Leg-Out	 2-3/8" x 2-3/8" x 1/4"	32"	○
8	T Section Leg-In	 2" x 2" x 1/4"	32"	○
9	Tubing - Square	 2" x 2" x 0.120"	63"∞	○●
10	Tubing - Rectangle	 2-3/4" x 1-1/4" x 0.080"	60"∞	○●
11	Solid - Round	 Ø1-3/8"	24"	○●
12	Schedule 40 Pipe	 1" SCH 40 2" SCH 40	14"∞ 40"∞	●
13	Tubing - Round	 Ø1" x 0.060" Ø2-3/4" x 0.080"	16"∞ 48"∞	●
14	C Section Leg-Out	 3"	32"	○●
15	C Section Leg-In	 3"	48"	○●

Capacity based on mild steel | ∞ Can be changed according to deformation
 ○ Standard Rolls | ● Special Rolls | X Special Support Rolls | ▲ Special Tools

Shaft Diameters: 1.96"

Roll Diameters: Top 6.37"; Bottom 5.98"

Motor Power: 2.0 HP

Turning Speed: 14 FPM

Dimensions: 32" L x 38" W x 60" H

Weight: 1102 lbs.

RMT Profile Rolls

A-ECO 196 H



STANDARD SPECIFICATIONS:

- Steel welded construction frame
- 3 Rolls are motor driven
- Hardened shafts from special steel material
- Top roll hydraulic moveable up-down
- Horizontal and vertical working position
- Standard rolls
- Guide rolls
- Brake motor equipped for the precision bending
- Mobile control panel

OPTIONS:

- Pipe / Tube bending rolls
- Profile bending rolls
- Angle bending rolls
- Digital Read-Out
- Optional lateral angle guides
- Optional stairway bending attachment
- NC control