



## SPECIFICATIONS

Prices may be listed on a separate quotation page.  
 Prices and specifications are subject to change without notice.  
 Prices **MIGHT NOT INCLUDE** freight, handling and applicable taxes.

**844.RMT.INFO**  
**www.RMTUS.com**

Profile Type			A-GIANT 944		Notes
			Dimensions	Min. Internal Diameter	
1	Solid - Square		5" x 5"	96"	○
2	Flat-Along Edge		8" x 2-3/4"	150"	○
3	Solid - Rectangle		15" x 3"	100"	○
4	Angle Leg-Out		8" x 8" 3/4"	120"	○●
5	Angle Leg-In		8" x 8" 3/4"	160"	○●
6	T Section Leg-Down		8" x 8" x 1"	120"	○
7	T Section Leg-Out		8" x 8" x 1"	120"	○
8	T Section Leg-In		8" x 8" x 1"	138"	○
9	Tubing - Square		8" x 8" x 3/8"	240"∞	○●
10	Tubing - Rectangle		12" x 4" x 3/8"	315"∞	○●
11	Solid - Round		Ø6"	120"	○●
12	Schedule 40 Pipe		10" SCH 40	200"∞	●
13	Tubing - Round		Ø12" x 0.250"	354"∞	●
14	C Section Leg-Out		C15-50#	120"	○●
15	C Section Leg-In		C15-50#	138"	○●
16	I Section Easy Way		S18-70#	138"	●
17	H Section Easy Way		W12-79#	158"	●
18	C Section Hard Way		C10-25#	473"	●
19	I Section Hard Way		S12-35#	473"	●
20	H Section Hard Way		W8-40#	276"	●

Capacity based on mild steel | ∞ Can be changed according to deformation  
 ○ Standard Rolls | ● Special Rolls | ✕ Special Support Rolls | ▲ Special Tools

Shaft Diameters: 9.44"

Roll Diameters: 27.55"

Motor Power: 60 HP

Turning Speed: 6-13 FPM

Dimensions: 166" L x 117" W x 126" H

Weight: 62832 lbs.

## RMT Profile Rolls A-GIANT 944



### STANDARD SPECIFICATIONS:

- Steel construction welded frame
- 3 Rolls are hydraulic powered by planetary gearbox separately
- Hardened and ground shafts made of high tensile special steel
- Rolls are hardened and ground
- Only horizontal working position
- Hardened standard rolls
- Two speed working system
- Mobile control panel
- 3 Axis hydraulic lateral angle guide rolls
- Digital Read-Outs (1pcs)

### OPTIONS:

- All kind of pipes, tubes, profile rolls and I, H and U beam attachments are available upon request
- Variable turning speed
- NC control