




S-FAB PDM17-24

Semiautomatic Pivot Type Double Miter Bandsaw



STANDARD

- Control Panel
- Blade Brush
- Hydraulic Vice
- Security Switch
- Height Adjustment Switch
- Siti Heavy Duty Gearbox
- Inverter
- Sensitive Pressure Control
- Hydromechanical Blade Tension
- Anti Vibration Cylinder
- Coolant Pump
- 4ft Roller Table

OPTIONAL

- Control Panel NC
- Hydraulic Blade Tension
- Microspray Cooling
- 10ft Roller Table
- 10ft Motorized Roller Table
- Laser Line

| S-FAB PDM 17-24 | | Metric | US |
|-----------------|--------------|--------------------|-------------------------|
| Capacity at 0° | Round | 440 mm | 17.3" in |
| | Flat (H x W) | 440 x 610 mm | 17.3" x 24" in |
| | Square | 440 mm | 17.3" in |
| Capacity at 30° | Round | 440 mm | 17.3" in |
| | Flat (H x W) | 440 x 500 mm | 17.3" x 19.7" in |
| | Square | 440 mm | 17.3" in |
| Capacity at 45° | Round | 410 mm | 16.1" in |
| | Flat (H x W) | 440 x 410 mm | 17.3" x 16.1" in |
| | Square | 410 mm | 16.1" in |
| Capacity at 60° | Round | 320 mm | 12.6" in |
| | Flat (H x W) | 440 x 250 mm | 17.3" x 9.8" in |
| | Square | 250 mm | 9.8" in |
| Capacity at-30° | Round | 440 mm | 17.3" in |
| | Flat (H x W) | 440 x 500 mm | 17.3" x 19.7" in |
| | Square | 440 mm | 17.3" in |
| Capacity at-45° | Round | 410 mm | 16.1" in |
| | Flat (H x W) | 440 X 410 mm | 17.3" x 16.1" in |
| | Square | 410 mm | 16.1" in |
| Capacity at-60° | Round | 320 mm | 12.6" in |
| | Flat (H x W) | 440 X 285 mm | 17.3" x 11.2" in |
| | Square | 285 mm | 11.2" in |
| Cutting Speeds | | 20- 100 m/min | 65- 328 ft/min |
| Band Dims. | | 5200 x 34 x 1.1 mm | 204.7 x 1.34 x 0.043 in |
| Main Motor | | 4 kW | 5.5 HP |
| Hydraulic Motor | | 0.55 kW | 3/4 HP |
| Weight | | 1540 kg | 3395 lbs |
| Machine Dims. | Length | 2800 mm | 111" in |
| | Width | 1210 mm | 48" in |
| | Height | 1870 mm | 74" in |