

STANDARD

- Control Panel NC
- Blade Brush
- Hydraulic Vice
- Hydraulic Feeding Vice
- Security Switch
- Height Adjustment Switch
- Siti Heavy Duty Gearbox
- Inverter
- Sensitive Pressure Control
- Hydromechanical Blade Tension
- Coolant Pump
- Anti Vibration Cylinder



OPTIONAL

- Hydraulic Blade Tension
- Hydraulic Top Clamping
- Dropsa Air/oil clean lubrication system
- Micromist Cooling

S-SMART P 9-9		Metric	US
Capacity at 0°	Round	320 mm	12.6" in
	Flat (H x W)	300 x 320 mm	11.8" x 12.6" in
	Square	300 mm	11.8" in
Cutting Speeds		20- 100 m/min	65- 328 ft/min
Band Dims.		3660 x 27 mm	144 x 1.06 in
Main Motor		2.2 kW	3 HP
Hydraulic Motor		0.37 kW	1/2 HP
Feed Motor		0.25 kW	1/3 HP
Weight		765 kg	1687 lbs
Machine Dims.	Length	1900 mm	75" in
	Width	850 mm	34" in
	Height	1300 mm	51" in


S-Smart P 9-9




Fiber Lasers



Press Brakes




Shears




Ironworkers



Plate Rolls




Angle Rolls



Bandsaws



Dishing Presses



Flanging Machines



Drilling Machines

"If you need a machine and don't buy it, you'll find that you have paid for it anyway, but don't have it."

Henry Ford

Revolution Machine Tools
385 N 700 W
North Salt Lake, UT 84054

www.RMTUS.com
info@rmtus.com

Phone: 844.RMT.INFO
844.768.4636

KYSON

844-768-4636 / www.RMTUS.com