

Standard

- Double Grinding Area
- Double Speed Robust Motor
- 60 Degree Miter Capability
- Easy-to-Use Quick Change Clamp
- Set of 7 Mandrels for Tubing Sizes 1", 1.25", 1.5", 1.75", 2", 2.5" and 3"

Optional

- Mandrels For All Tube Sizes Ranging From 1" to 3"
- Mandrels For All Pipe Sizes Ranging From 1.06" to 2.875"



TN-FAB 4


TN-FAB 4		Metric	US
Capacity at 0°	Capacity	20 - 76 mm	0.78 - 3"
	Motor (Double Speed)	3 kW	4 Hp
	Motor Speed	2800 RPM	2800 RPM
Belt Speeds		30 mm/sec	1.2 in/sec
Belt Measurements		2000 x 100 mm	6 ft 7" x 4"
Noise Emission		83-87 dB(A)	83-87 dB(A)
Weight		190 kg	419 lbs
Machine Dims.	Length	1000 mm	3 ft 4"
	Width	500 mm	1 ft 8"
	Height	1050 mm	3 ft 5"




Fiber Lasers



Press Brakes



Shears



Ironworkers






Plate Rolls




Angle Rolls



Bandsaws



Dishing Presses



Flanging Machines



Drilling Machines

"If you need a machine and don't buy it, you'll find that you have paid for it anyway, but don't have it."

Henry Ford

Revolution Machine Tools
385 N 700 W
North Salt Lake, UT 84054

www.RMTUS.com
info@rmtus.com

Phone: 844.RMT.INFO
844.768.4636

KYSON

844-768-4636 / www.RMTUS.com