

## STANDARD

- Control panel
- Blade brush
- Hydraulic vise
- PLC controller encoder
- Security switch
- SITI heavy duty gearbox
- Infinite variable speed inverter
- Sensitive pressure control
- Hydromechanical blade tension
- Coolant pump
- Mechanical top clamping
- Anti vibration cylinder
- 4ft roller table control panel

## OPTIONAL

- Hydraulic blade tensioning
- Dropsa air/oil clean lubrication system
- Hydraulic top clamping
- Micromist cooling
- 10ft roller table



| S-SMART P 9-9   |              | Metric        | US             |
|-----------------|--------------|---------------|----------------|
| Capacity at 0°  | Round        | 230 mm        | 9" in          |
|                 | Flat (H x W) | 240 x 230 mm  | 9.4" x 9" in   |
|                 | Square       | 230 mm        | 9.0" in        |
| Cutting Speeds  |              | 20- 100 m/min | 65- 328 ft/min |
| Band Dims.      |              | 3660 x 27 mm  | 144 x 1.06 in  |
| Main Motor      |              | 1.5 kW        | 2 HP           |
| Hydraulic Motor |              | 0.37 kW       | 1/2 HP         |
| Feed Motor      |              | 0.25 kW       | 1/3 HP         |
| Weight          |              | 530 kg        | 1166 lbs       |
| Machine Dims.   | Length       | 1700 mm       | 67" in         |
|                 | Width        | 800 mm        | 31" in         |
|                 | Height       | 1160 mm       | 46" in         |

# S-Smart P 9-9