

Standard

- Double grinding area
- Double speed robust motor
- 60 degree miter capability
- Easy to use quick change clamp
- Set of 7 mandrels for tubing sizes 1", 1.25", 1.5", 1.75", 2", 2.5" and 3"
- Offset notching capability

Optional

- Mandrels for all tube sizes ranging from 1" - 3"
- Mandrels for all pipe sizes ranging from 1.06" - 2.875"



TN-FAB 4

208 or 230 Volt 3 Phase (1 Phase 220V Power Available - Please Consult RMT)


TN-FAB 4		Metric	US
Capacity at 0°	Capacity	20-76 mm	0.78 - 3"
	Motor (Double Speed)	3 kW	4 HP
	Motor Speed	2800 RPM	2800 RPM
Belt Speeds		30 mm/sec	1.2 in/sec
Belt Measurements		2000 x 100 mm	6' 7" x 4"
Noise Emission		83-87 dB(A)	83-87 dB(A)
Weight		190 kg	419 lbs
Machine Dims.	Length	1000 mm	3' 4"
	Width	500 mm	1' 8"
	Height	1050	3' 5"



Hydraulic Presses




Fiber Lasers




PSM Pipe Lathe



Press Brakes



Shears



Ironworkers



Plate Rolls



Angle Rolls



Bandsaws



Dishing Presses



Flanging Machines



Drilling Machines

"If you need a machine and don't buy it, you'll find that you have paid for it anyway, but don't have it."

Henry Ford

Revolution Machine Tools
385 N 700 W
North Salt Lake, UT 84054

www.RMTUS.com
info@rmtus.com

Phone: 844.RMT.INFO
844.768.4636

KYSON

844-768-4636 / www.RMTUS.com