




S-FAB VDM 18-28

Semi-Automatic Double Miter Vertical Tilt-Frame Bandsaw



STANDARD

- Speed Controller
- Precise Cutting Adjustment
- Control Panel
- Engine Oil Pump
- Hydro mechanical Strip Tensioning
- Cover Switch
- Hydraulic Vise
- Cutting Width Adjustment Lever
- Powerful Reducer
- Linear Guide
- Sawdust Brush
- Optical Height Adjustment
- 5° Inclined Head
- Hydraulic Angle Stabilization

OPTIONAL

- Driver Servo Motor
- Chip Conveyor Motor
- Hydraulic blade tension
- Hydraulic top clamping
- Dropsa air/oil clean lubrication system
- Micromist cooling
- Laser line

S-FAB VDM 18-28		Metric	US
Capacity at 0°	Round	460 mm	18" in
	Flat (H x W)	460 x 710 mm	18" x 28" in
	Square	460 mm	18" in
Capacity at 30°	Round	460mm	18" in
	Flat (H x W)	460 x 590 mm	18" x 23" in
	Square	460 mm	18" in
Capacity at 45°	Round	460 mm	18" in
	Flat (H x W)	460 x 450 mm	18" x 17.7" in
	Square	460 mm	18" in
Capacity at 60°	Round	275 mm	10.8" in
	Flat (H x W)	460 x 275 mm	18" x 10.8" in
	Square	275 mm	10.8" in
Capacity at -30°	Round	460 mm	18" in
	Flat (H x W)	460 x 590 mm	18" x 23" in
	Square	460 mm	18" in
Capacity at -45°	Round	460 mm	18" in
	Flat (H x W)	460 x 480 mm	18" x 19" in
	Square	460 mm	18" in
Capacity at -60°	Round	325 mm	12.8" in
	Flat (H x W)	460 x 325 mm	18" x 12.8" in
	Square	460 mm	18" in
Cutting Speeds		15 - 120 m/min	49 - 394 ft/min
Band Dims.		6000 x 34 mm	236.2" x 1.3" in
Main Motor		4 kW	5.4 HP
Hydraulic Motor		2.2 kW	3 HP
Weight		2750 kg	6063 lbs
Machine Dims.	Length	3250 mm	1281" in
	Width	2150 mm	85" in
	Height	2800 mm	110" in